

# WIRE FOR VINEYARD AND AGRICULTURE

**FILAR®**



## PRODUCT RANGE

**FILAR® 400**

Extrasoft malleable normal galvanisation.

**FILAR® CLASSIC**

Malleable triple galvanisation.

**FILAR® AL900**

Technical steel wire, high-tensile with zinc 95% + aluminium 5%, coating Class A.

**FILAR® AL900eco**

Technical steel wire, high-tensile with zinc 95% + aluminium 5%, coating Class B.

**FILAR® HR**

High-tensile wire, 3% elongation, triple galvanisation.

**FILAR® AL1200eco**

Extra high strength steel coated zinc 95% + aluminium 5%, coating Class B.

**FILAR® AL1500**

Extra high strength steel, 3% elongation, coated zinc 95% + aluminium 5%, coating Class A.

**FILAR® SINTERBERG**

Technical plastic coated steel wire manufactured with SINTERBERG® technology.



## TECHNICAL DATA

**STELL – UNI EN 16120-2**

from C4D to C86D

**DIAMETERS RANGE**

from 0,80 to 8,0 mm

**COATING – UNI EN 10244-2 T1-T2**

zinc 99,995% • Class A/B/C/D

zinc 95% + aluminium 5% • Class A/B/C/D

zinc 90% + aluminium 10% • Class A/B/C/D

## PACKAGING

**RING**

Ø diameters (mm)	weight (kg)
0,80-8,00	25-100

**SPOOLED RING**

Ø diameters (mm)	weight (kg)
1,60-3,50	25

**METAL SUPPORT**

Ø diameters (mm)	weight (kg)
1,60-3,50	25