

WIRE FOR VINEYARD AND AGRICULTURE

FILAR[®]UR



FEATURES

High resistance vine wire, **elongation 3% super rich galvanization**.
Improved packaging increases unwinding speed and **facilitates handling**.



TECHNICAL DETAILS

STEEL - UNI EN 16120-2

from C4D to C86D

DIAMETERS RANGE

from 1,60 to 8,00 mm

TENSILE STRENGTHfrom 850 to 950 N/mm²**COATING - UNI EN 10244-2 T2**

zinc 99,995% • Class A

PACKAGING**RING**

Ø range (mm)	weight (kg)
1,60-8,00	25-100

SPOOLED RING

Ø range (mm)	weight (kg)
1,60-3,50	25

METAL SUPPORT

Ø diameters (mm)	weight (kg)
1,60-3,50	25

PRODUCTION RANGE

Ø (mm)	J.d.P.	Development
--------	--------	-------------

1,60	11	64,20
1,80	12	50,50
2,00	13	41,10
2,20	14	33,80
2,40	15	28,60
2,80		20,80
3,10		16,97
3,50	18	13,20
4,00	19	10,10
4,50	20	8,00
5,00	21	6,50
5,50	22	5,40
6,00	23	4,50
6,50	24	3,80
7,00	25	3,30
7,50	26	2,90
8,00	27	2,60