

GALVANIZED WIRE



USES

- Wire for rockfall protection systems, mesh and gabions
- Wire for electrowelded mesh and fences
- Wire for fencing
- Wire for cable armouring
- Wire for ropes
- Wire for springs
- Wire for lightning
- Wire for protection bucket and paint rollers
- Wire for bent metal elements for the automotive industry
- Wire for bailing of cellulose
- Chain link fences for sport centers



TECHNICAL DATA

STEEL - UNI EN 16120-2

from C4D to C86D

DIAMETERS

from 0,8 to 16,0 mm

TENSILE STRENGTH

from 380 a 2.000 N/mm2

COATING - UNI EN 10244-2 T1

zinc 99,995% - class A/B/C/D

Upon specific request, it is possible to find an agreement on packaging, diameter, coating mass and tensile strength.

PACKAGING

SPOOL

Ø diameters (mm)	weight (kg)
2,00-11,00	1000-2000

RING

Ø diameters (mm)	weight (kg)
0,80-7,00	25-100
8,00-10,00	40-50

ORBIT COIL

Ø diameters (mm)	weight (kg)
0,80-1,50	200-250
1,60-12,00	650-2400

GALVANIZED WIRE ROD

Ø diameters (mm)	weight (kg)
5,50-16,00	2000-2400

COATING UNI EN 10244-2 T1

DIAMETER (mm)	CLASSES (g/m2)			
	A	B	C	D
0,80-0,90	145	70	50	20
0,90-1,00	155	70	55	25
1,00-1,20	165	80	60	25
1,20-1,40	180	90	65	25
1,40-1,65	195	100	70	30
1,65-1,85	205	100	75	30
1,85-2,15	215	115	80	40
2,15-2,50	230	125	85	45
2,50-2,80	245	125	95	45
2,80-3,20	255	135	100	50
3,20-3,80	265	135	105	60
3,80-4,40	275	135	110	60
4,40-5,20	280	150	110	70
5,20-8,20	290		110	80
8,20-10,00	300		110	80