

REDRAWN GALVANIZED WIRE



USES

- Wire for springs
- Wire for protection bucket and paint rollers
- Wire for bent metal elements for the automotive industry



TECHNICAL DATA

STEEL - UNI EN 16120-2

from C4D to C86D

DIAMETERS

from 1,88 to 11,0 mm

TENSILE STRENGTH

from 380 to 2000 N/mm²

COATING

| | |
|---------------------------|-------------------|
| zinc 99,995% | UNI EN 10244-2 T1 |
| zinc 95% + aluminium 5% | UNI EN 10244-2 T2 |
| zinc 90 % + aluminium 10% | UNI EN 10244-2 T2 |

Upon specific request, it is possible to find an agreement on packaging, diameter, coating mass and tensile strength.

PACKAGING

CARRIER

| | |
|------------------|-------------|
| Ø diameters (mm) | weight (kg) |
| 1,88-11,00 | 500-1000 |

SPOOL

| | |
|------------------|-------------|
| Ø diameters (mm) | weight (kg) |
| 2,00-11,00 | 1000-2000 |

RING

| | |
|------------------|-------------|
| Ø diameters (mm) | weight (kg) |
| 1,80-7,00 | 25-100 |
| 8,00-11,00 | 40-50 |

ORBIT COIL

| | |
|------------------|-------------|
| Ø diameters (mm) | weight (kg) |
| 1,80-6,0 | 650-1100 |
| 4,00-11,00 | 800-1500 |