

# WIRE FOR VINEYARD AND AGRICULTURE

**FILAR<sup>®</sup> AL 900**



## FEATURES

Technical steel wire, **high-tensile** with **zinc 95% + aluminium 5%**, **coating class A**.

The exceptional stability and **high mechanical resistance** make **FILAR<sup>®</sup> AL900** the ideal product for mechanical harvesting and does not require periodic tensioning.



## TECHNICAL DETAILS

### STELL - UNI EN 16120-2

from C4D to C86D

### DIAMETERS RANGE

from 1,60 to 8,00 mm

### TENSILE STRENGTH

from 850 to 950 N/mm<sup>2</sup>

### ELONGATION

5%

### COATING - UNI EN 10244-2 T2

zinc 95% + aluminium 5% • class A

zinc 90% + aluminium 10% • class A

## PACKAGING

### RING

Ø range (mm) weight (kg)  
1,60-8,00 25-100

### SPOOLED RING

Ø range (mm) weight (kg)  
1,60-3,50 25

### METAL SUPPORT

Ø range (mm) weight (kg)  
1,60-3,50 25

## PRODUCTION RANGE

Ø (mm)	J.d.P.	Development
1,60	11	64,20
1,80	12	50,50
2,00	13	41,10
2,20	14	33,80
2,40	15	28,60
2,80		20,80
3,10		16,97
3,50	18	13,20
4,00	19	10,10
4,50	20	8,00
5,00	21	6,50
5,50	22	5,40
6,00	23	4,50
6,50	24	3,80
7,00	25	3,30
7,50	26	2,90
8,00	27	2,60