

WIRE FOR VINEYARD AND AGRICULTURE

FILAR[®]UR



FEATURES

High resistance vine wire, **elongation 3% super rich galvanization.**
Improved packaging increases unwinding speed and **facilitates handling.**



TECHNICAL DETAILS

STEEL - UNI EN 16120-2

from C4D to C86D

DIAMETERS RANGE

from 1,60 to 8,00 mm

TENSILE STRENGTH

from 850 to 950 N/mm²

COATING - UNI EN 10244-2 T2

zinc 99,995% • class A

PACKAGING

RING

Ø range (mm) weight (kg)
1,60-8,00 25-100

SPOOLED RING

Ø range (mm) weight (kg)
1,60-3,50 25

METAL SUPPORT

Ø range (mm) weight (kg)
1,60-3,50 25

PRODUCTION RANGE

Ø (mm)	J.d.P.	Development
1,60	11	64,20
1,80	12	50,50
2,00	13	41,10
2,20	14	33,80
2,40	15	28,60
2,80		20,80
3,10		16,97
3,50	18	13,20
4,00	19	10,10
4,50	20	8,00
5,00	21	6,50
5,50	22	5,40
6,00	23	4,50
6,50	24	3,80
7,00	25	3,30
7,50	26	2,90
8,00	27	2,60